# SAFETY DATA SHEET KEROSENE

Product Name: KEROSENE

Date of Issue: MAY 2017 Page 1 of Total 7

SECTION 1 – STATEMENT OF CHEMICAL PRODUCT AND COMPANY IDENTIFICATION				
SUPPLIER:	GLEAM ALL	GLEAM ALL		
ADDRESS:	Unit 4, 12 Commercial Drive, Ashm	Unit 4, 12 Commercial Drive, Ashmore, Qld 4214 Australia.		
Trade Name:	KEROSENE			
TELEPHONE:	(07) 5531 1544	FAX:	(07) 5591 1800	
AH EMERGENCY TELEPHONE:	13 1126 in Australia	Product Code:		
Substance:	Solvent	Product Use:	Fuel/cleaning solvent	
Creation Date:	May 2017	Revision Date:	May 2022	

SECTION 2 – HAZARDS IDENTIFICA	ATION		
Classification of the substance or	mixture		
Poisons Schedule	S5 (LIQUID HYDROCARBONS)		
Dangerous Goods	Classified as Dangerous Goods class 3 Flammable		
GHS Classification	Eye Irritation Category 2A		
	Skin Irritation Category 2		
	Specific Target Organ Toxicity 3		
	Flammable Liquids Category 3		
	Aspiration Hazard Category 1		
	Carcinogenicity Category 2		
Label elements			
GHS label pictograms	GHS07 GHS08 GHS02		
Signal word	DANGER		
Hazard statement(s)			
H319	Causes serious eye irritation.		
H315	Causes skin irritation.		
H335	May cause respiratory irritation.		
H226	Flammable liquid and vapour.		
H304	May be fatal if swallowed and enters airways.		
H351	Suspected of causing cancer.		
Precautionary statement(s): Gene	eral		
P102	Keep out of reach of children.		
P103	Read label before use.		
Precautionary statement(s): Prev	s): Prevention		
P201	Obtain special instructions before use.		
P202	Do not handle until all safety precautions have been read and understood.		
P210	Keep away from heat/sparks/open flames/hot surfaces. — No smoking.		
P233	Keep container tightly closed.		
P240	Ground/bond container and receiving equipment.		
P241	Use explosion-proof electrical/ventilating/lighting//equipment.		
P242	Use only non-sparking tools.		
P243	Take precautionary measures against static discharge.		

### SAFETY DATA SHEET

Product Name: KEROSENE

Date of Issue: MAY 2017 Page 2 of Total 7

P261	Avoid breathing fume/mist/vapours/spray.		
P271	Use only outdoors or in a well-ventilated area.		
P264	Wash thoroughly after handling.		
P280	Wear protective gloves/protective clothing/eye protection/face protection.		
P281 Use personal protective equipment as required.			
Precautionary statement(s): Resp	oonse		
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if		
	present and easy to do. Continue rinsing.		
P337 + P313	If eye irritation persists: Get medical advice/attention.		
P301 + P310	IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.		
P331	Do NOT induce vomiting.		
P304 + P340	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for		
	breathing.		
P312	Call a POISON CENTER or doctor/physician if you feel unwell.		
P302 + P352	IF ON SKIN: Wash with plenty of soap and water.		
P332 + P313 If skin irritation occurs: Get medical advice/attention.			
P362 Take off contaminated clothing and wash before reuse.			
P308 + P313   IF exposed or concerned: Get medical advice/ attention.			
P321 Specific treatment (see First Aid Measures on Safety Data Sheet).			
P370 + P378 In case of fire: use foam, water spray or fog, dry chemical powder or carb			
	extinction. Do not use water in a jet.		
Precautionary statement(s): Store	age		
P403 + P235 + P233	Store in a well-ventilated place. Keep cool. Keep container tightly closed.		
P405 Store locked up.			
Precautionary statement(s): Disposal			
P501 Dispose of contents/ container in accordance with local regulations.			
Note			
IMPORTANT	This SDS and the Hazard Classifications contained therein, only apply to the product in its		
	concentrated form, as supplied. When diluted to 1:10 or greater they no longer apply.		
	However, good hygiene and housekeeping practices should be adhered to.		

Ingredients:	CAS Number:	Proportion:
Low Aromatic White Spirit - Naphtha	64742-82-1	>60% w/w
(petroleum), hydrodesulfurized heavy		
With components:		
1,2,4-Trimethylbenzene	95-63-6	< 10% w/w
1,3,5-Trimethylbenzene	108-67-8	< 10% w/w
Naphthalene	91-20-3	< 10% w/w
Xylene, Mixed Isomers	1330-20-7	< 10% w/w
Note – contains < 0.1% benzene		

NOTE: Ingredients determined not to be hazardous are present in concentrations that do not exceed the relevant cut-off concentrations as found from NOHSC publication "List of Designated Hazardous Substances" or have been found NOT to meet the criteria of a hazardous substance as defined in the NOHSC publication "Approved Criteria for Classifying Hazardous Substances", or have been found NOT to meet the criteria of a dangerous substance as defined in the GLOBALLY HARMONIZED SYSTEM OF CLASSIFICATION AND LABELLING OF CHEMICALS (GHS), 4th edition United Nations 2011. Listed ingredients may be below the cut-off concentrations for classification as hazardous, but are listed for information purposes and for additive effects.

SECTIO	MA - E	ΙΡςτ ΔΙΓ	ΜΕΔΟ	IIRFS

Inhalation	Keep victim calm and remove to fresh a	ir if safe to do so. If rapid recovery does not occur,

## **SAFETY DATA SHEET**

Product Name: KEROSENE

Date of Issue: MAY 2017 Page 3 of Total 7

	transport to nearest medical facility for additional treatment.		
Skin contact	Immediately wash contaminated skin with plenty of soap and water. Remove contaminated clothing and wash before re-use. Seek medical advice (e.g. doctor) if irritation, burning or redness persists.		
Eye contact	If in eyes, hold eyelids apart and flush the eyes continuously with running water. Remove contact lenses. Continue flushing until advised to stop by the Poisons Information Centre or a doctor, or for at least 15 minutes. If symptoms persist, seek medical attention.		
Ingestion	If swallowed, do NOT induce vomiting. Transport to nearest medical facility for additional treatment. If vomiting occurs spontaneously, keep head below hips to prevent aspiration.		
Advice to Doctor	Treat symptomatically.		
Scheduled Poisons	Poisons Information Centre in each Australian State capital city or in Christchurch, New Zealand can provide additional assistance for scheduled poisons. (Phone Australia 131126 or New Zealand 0800 764 766).		
First Aid Facilities	Eye wash station. Normal washroom facilities.		

SECTION 5 – FIRE FIGHTING MEASURES		
Fire and Explosion	Flammable liquid. In use, may form flammable/explosive vapour air mixture. If involved in a fire	
Hazards	will emit toxic fumes.	
Extinguishing Media	Foam, water spray or fog, dry chemical powder or carbon dioxide. Do not use water in a jet.	
Fire Fighting	Keep containers exposed to extreme heat cool with water spray. Fire fighters to wear self-	
	contained breathing apparatus if risk of exposure to products of combustion or decomposition.	
Flash Point	Flash point ca 38 °C	

SECTION 6 – ACCIDENTAL RELEASE MEASURES		
<b>Emergency Procedures</b>	HAZCHEM code: 3Y	
	3 = use FOAM to fight fires.	
	Y = Yes – risk of violent reaction, recommend full fire kit and breathing apparatus for fire only,	
	CONTAIN.	
	Shut off engine and electrical equipment off. No smoking or naked lights within 50 metres.	
	Move people from immediate area; keep upwind. Send messenger to notify fire brigade and	
	police. Tell them location, material quantity, UN number and emergency contact. Indicate	
	condition of vehicle and damage or injuries observed. Warn other traffic.	
	Occupational Release	
	Minor spills do not normally need any special clean-up measures. In the event of a major spill,	
	prevent spillage from entering drains or water-courses. For large spills, or tank rupture,	
	consider initial evacuation distance of 200 metres in all directions. Stop leak if safe to do so.	
	Remove all ignition sources. If available, use water spray to disperse vapour. Wear appropriate	
	protective equipment as in section 8 below to prevent skin and eye contamination. Spilt	
	material may result in a slip hazard and should be absorbed into dry, inert material (e.g. sand,	
	earth or vermiculite), which then can be put into appropriately labelled drums for disposal by	
	an approved agent according to local conditions. Residual deposits will remain slippery. Wash	
	area down with excess water. If contamination of sewers or waterways has occurred advise	
	the local emergency services. In the event of a large spillage notify the local environment	
	protection authority or emergency services.	

# SAFETY DATA SHEET KEROSENE

Product Name: KEROSENE

Date of Issue: MAY 2017 Page 4 of Total 7

Handling	Avoid skin or eye contact with concentrate. Wear protective clothing when risk of exposure occurs. Avoid contact with incompatible materials. When handling, DO NOT eat, drink or smoke. Keep containers closed at all times. Avoid physical damage to containers. Always wash hands with soap and water after handling. Work clothes should be laundered. Launder contaminated clothing before re-use.
Storage	Store in a cool, dry, well-ventilated area, out of direct sunlight. Protect from freezing. Store in suitable, labelled containers. Keep containers tightly closed. Store away from incompatible materials and ignition sources. Ensure that storage conditions comply with applicable local and national regulations.

<b>Exposure Limits</b>	National Occupational Exposure Limits, as published by National Occupational Health & Safety		
•	Commission:		
	Time-weighted Average (TWA):		
	None established for product.		
	In the absence of data from National Occupational Health & Safety Commission (NOHSC)		
	Worksafe Australia use - Mineral Spirits 175-220 HSPA: 350mg/m³ TWA (8hr)  Short Term Exposure Limit (STEL):		
	None established for product.		
Ventilation	Ensure ventilation is adequate to maintain air concentrations below exposure standards. Avoid		
	generating mists of the product. Use only in a well-ventilated area. Ensure airflow, where this		
	product is used, is directed away from the operators.		
Personal Protective	Use good occupational work practice. The use of protective clothing and equipment depends		
Equipment	upon the degree and nature of exposure. The following protective equipment should be		
	available;		
Eye Protection	Safety glasses with full face shield should be used for handling concentrate in quantity, cleaning		
	up spills, decanting, etc. Eye protection devices should conform to relevant regulations. Eye		
	protection should conform with Australian/New Zealand Standard AS/NZS 1337 - Eye Protectors		
	for Industrial Applications.		
Hand Protection	Use solvent resistant gloves, nitrile for longer term protection or PVC and neoprene for		
	incidental splashes – to handle in quantity, clean up spills, decanting, etc. Final choice of		
	appropriate gloves will vary according to individual circumstances. i.e. methods of handling or		
	according to risk assessments undertaken. Occupational protective gloves should conform to		
	relevant regulations. Reference should be made to AS/NZS 2161.1: Occupational protective		
	gloves - Selection, use and maintenance.		
Body Protection	Suitable protective workwear, e.g. rubber or plastic apron, sleeves, boots and cotton overalls		
- C-2-	buttoned at neck and wrist are recommended. Chemical resistant apron is recommended where		
	large quantities are handled.		
Respirator	If work practices do not maintain airborne level below the exposure standard, use appropriate		
The spirate of	respiratory protection equipment. When using respirators, select an appropriate combination of		
	mask and filter. Select a filter for organic gases and vapours (boiling point > 65°C). Respirators		
	should comply with AS1716 or an equivalent approved by a state/territory authority.		

SECTION 9 – PHYSICAL AND CHEMICAL PROPERTIES			
Physical State	Non-viscous liquid	Colour	Clear
Odour	characteristic odour	Specific Gravity	0.80 − 0.90 @ 25 ºC
<b>Boiling Point</b>	Typical 145 - 300 °C	Freezing Point	Data not available
Vapour Pressure	Not available	Vapour Density	Not available
Flash Point	Approximately 38 °C	Flammable Limits	1.0 - 6.0%
Water Solubility	Miscible	рН	6.5 – 7.5 @ 1%

## SAFETY DATA SHEET

Product Name: KEROSENE

Date of Issue: MAY 2017 Page 5 of Total 7

Volatile Organic		Per Cent Volatile	
Compounds (VOC)	Ca 90 % v/v		Ca 90 % v/v
Viscosity	Not available	Odour Threshold	Not available

SECTION 10 – STABILITY AND REACTIVITY	
Reactivity	Stable at normal temperatures and pressure.
<b>Conditions to Avoid</b>	Avoid heat, sparks, open flames and other ignition sources.
Incompatibilities	Strong oxidising agents.
Hazardous	Thermal decomposition is highly dependent on conditions. A complex mixture of airborne solids,
Decomposition	liquids, gases, including carbon monoxide, carbon dioxide and other organic compounds will be
	evolved when this material undergoes combustion or thermal or oxidative degradation.

POTENTIAL HEALTH EFFECT	rs
No adverse health effects e	expected if the product is handled in accordance with this Safety Data Sheet and the product label.
Symptoms or effects that n	nay arise if the product is mishandled and overexposure occurs are:
Inhalation	Breathing of high vapour concentrations may cause central nervous system depression resulting in dizziness, light-headedness, headache, nausea and loss of coordination. Continuous inhalation may result in unconsciousness and death.
Skin contact	May include redness, itching and swelling, burning sensation, blisters.
Eye contact	Concentrated product causes eye irritation. Eye contact with concentrate will cause stinging, blurring, tearing.
Ingestion	May cause irritation to the mouth, throat, oesophagus and stomach with symptoms of nausea, abdominal discomfort, vomiting and diarrhoea, coughing, choking, wheezing, difficulty in breathing, chest congestion, shortness of breath, and/or fever. Aspiration into the lungs when swallowed or vomited may cause chemical pneumonitis which can be fatal.
Chronic exposure	No known effects.
Toxicology Information	Not toxic, based on ingredients. Oral LD50 (calculated): >10,000 mg/L LD50 Dermal (rat) > 2000 mg/kg LC50 Inhalation greater than near-saturated vapour concentration (rat, 4h).
Carcinogen Status	
NOHSC	No significant ingredient is classified as carcinogenic by NOHSC.
NTP	No significant ingredient is classified as carcinogenic by NTP.
IARC	Naphthalene - Classified by the International Agency for Research on Cancer (IARC) as a Group 2B. Group 2B – The agent is possibly carcinogenic to humans.
Respiratory sensitisation	Not expected to be a respiratory sensitizer.
Skin Sensitisation	Not expected to be a skin sensitizer.
Germ cell mutagenicity	Not considered to be a mutagenic hazard.
Reproductive Toxicity	Not considered to be toxic to reproduction.
STOT-single exposure	Inhalation of vapours or mists may cause irritation to the respiratory system.
STOT-repeated exposure	Central nervous system: repeated exposure affects the nervous system. Effects seen at high doses only. Auditory system: prolonged and repeated exposures to high concentrations have resulted in hearing loss in rats. Solvent abuse and noise interaction in the work environment may cause hearing loss.
Aspiration Hazard	Aspiration into the lungs when swallowed or vomited may cause chemical pneumonitis which can be fatal.

## SAFETY DATA SHEET

Product Name: KEROSENE

Date of Issue: MAY 2017 Page 6 of Total 7

Eco-toxicity	Toxic to aquatic life with long-lasting effects.
Product (as sold)	Acute Aquatic Toxicity - 2 /Chronic Aquatic Toxicity – 2
	Expected to be harmful: 10 < LC/EC/IC50 <= 100mg/l
Persistence and	Riadamadahla Quidiasa ku uhata ahamisal maatiana in sin
degradability	Biodegradable. Oxidises by photo-chemical reactions in air.
Bio accumulative	Handle and additional and the second of the
potential	Has the potential to bio-accumulate.
Mobility in soil	Floats on water.
Other adverse effects	Not available
<b>Environmental Protection</b>	Do not discharge this material into waterways.

#### SECTION 13 – DISPOSAL CONSIDERATIONS

Dispose of waste according to applicable local and national regulations. Do not allow into drains or watercourses or dispose of where ground or surface waters may be affected. Wastes including emptied containers are controlled wastes and should be disposed of in accordance with all applicable local and national regulations.

SECTION 14 – TRANSPORT	INFORMATION
Labels Required	
ADG	PLANMABLE LIQUID
	Classified as Dangerous Goods class 3
<b>IMDG Marine Pollutant</b>	No
HAZCHEM	3Y
Land Transport (ADG)	
UN Number	1223
Proper Shipping Name	KEROSENE
ADG Code	3
HAZCHEM Code	3Y
<b>Special Provisions</b>	None allocated.
Packing Group	lli
Packaging Method	3.8.3 RT1
Segregation	Segregation Class 3 – Flammable liquid shall not be loaded in the same vehicle or packed in the same freight container with: Class 1, Explosives
	Class 2.1, Flammable Gases, if both the Class 3 and Class 2.1 dangerous goods are in bulk Class 2.3, Toxic Gases
	Class 4.2 Spontaneously Combustible Substances
	Class 5.1 Oxidising Agents and Class 5.2, Organic Peroxides
	Class 6 Toxic Substances (where the flammable liquid is nitromethane)
	Class 7 Radioactive Substances.
	Foodstuff and foodstuff empties.

SECTION 15 – REGULATORY INFORMATION		
GHS Classification	Classified as Hazardous according to the Globally Harmonised System of Classification and	
	labelling of Chemicals (GHS) including Work, Health and Safety regulations, Australia.	
SUSMP	S5 (LIQUID HYDROCARBONS)	

## SAFETY DATA SHEET

Product Name: KEROSENE

Date of Issue: MAY 2017 Page 7 of Total 7

ADG Code	UN 1223
AICS	All ingredients present on AICS.

Issue Date	8 <sup>th</sup> May 2017
Version Number	V 2.0 GHS classification
Abbreviations and	ADG Code: Australian Code for the Transport of Dangerous Goods by Road and Rail.
acronyms	AICS: Australian Inventory of Chemical Substances.
•	CAS Number: Chemical Abstracts Service Registry Number.
	GHS: Globally Harmonized System of Classification and Labelling of Chemicals
	HAZCHEM: An emergency action code of numbers and letters which gives information to emergency
	services.
	HSIS: Hazardous Substances Information System
	IARC: International Agency for Research on Cancer.
	NOHSC: National Occupational Health and Safety Commission.
	NTP: National Toxicology Program (USA).
	SDS: Safety Data Sheet
	STEL: Short Term Exposure Limit.
	<b>SUSMP</b> : Standard for the Uniform Scheduling of Medicines and Poisons.
	TWA: Time Weighted Average.
	UN Number: United Nations Number.
Literature references	Preparation of Safety Data Sheets for Hazardous Chemicals – Code of Practice ( Safe Work Australia)
	GHS Hazardous Chemical Information List (Safe Work Australia)
	Guidance on the Classification of Hazardous Chemicals under the WHS Regulations.
	Global Harmonized System of Classification and Labelling of Chemicals (GHS)
	"Australian Exposure Standards". Safework Australia
	Australian Code For The Transport Of Dangerous Goods By Road And Rail
	Standard for the Uniform Scheduling of Medicines and Poisons
	Material Safety Data Sheets – individual raw materials – Suppliers
	HSIS – Hazardous Substance Information System – National Safe Work Australia Data Base.
	HCIS – Hazardous Chemical Information System – National Safe Work Australia Data Base.
Disclaimer	This MSDS summarizes at the date of issue our best knowledge of the health and safety hazard information of thi product, and in particular how to safely handle and use this product in the workplace. Since the supplier cannot anticipate or control the conditions under which the product may be used, each user must, prior to usage, review thi MSDS in the context of how the user intends to handle and use the product in the workplace. If clarification or further information is needed to ensure that an appropriate assessment can be made, the user should contact this supplier.